

## **Hose Reels**

# **Levelwind™ Series - Auto-Rewind**


Retractable hose reels offering efficient cost hose storage for all markets.

- Levelwind<sup>™</sup> Technology is a unique winding system that automatically layers the hose back and forth across the reel. This ensures that the hose is coiled smoothly and easily.
- · Hose, lead-in hose and mounting bracket included with each reel.
- Two year warranty.

#### Air

- These models are designed to be used with air tools.
- · Hose material is PVC.

Hose Size/Length	Max. Working Pressure	Temp. Range (F°)	Reel Inlet GHT	Source Hose	Discharge Hose		
Compressed Air							
3/8" x 50'	350 PSI	0° to 140°	3/4" - 11-1/2 (M)	1/4" NPT (M)	1/4" NPT (M)		
3/8" x 75'	350 PSI	0° to 140°	3/4" - 11-1/2	1/4" NPT (M)	1/4" NPT (M)		
1/2" x 50'	300 PSI	0° to 150°*	3/4" - 11-1/2	1/2" NPT (M)	1/2" NPT (M)**		
	Size/Length Air 3/8" × 50' 3/8" × 75'	Size/Length         Pressure           Air         3/8" x 50'         350 PSI           3/8" x 75'         350 PSI	Size/Length         Pressure         Range (F°)           Air         3/8" x 50'         350 PSI         0° to 140°           3/8" x 75'         350 PSI         0° to 140°	Size/Length         Pressure         Range (F°)         Reel Inlet GHT           Air           3/8" x 50'         350 PSI         0° to 140°         3/4" - 11-1/2 (M)           3/8" x 75'         350 PSI         0° to 140°         3/4" - 11-1/2	Size/Length         Pressure         Range (F°)         Reel Inlet GHT         Hose           Air           3/8" x 50'         350 PSI         0° to 140°         3/4" - 11-1/2 (M)         1/4" NPT (M)           3/8" x 75'         350 PSI         0° to 140°         3/4" - 11-1/2         1/4" NPT (M)		



<sup>\*\*3/4&</sup>quot; GHT male garden hose adapter included

Model L8335 is ideal for high volume air tools. Also set-up for water applications.



Part No. L8335

#### Water

· Hose material is PVC.

Part No.	Hose Size/Length	Max. Working Pressure	Temp. Range (F°)	Reel Inlet MNPT	Source Hose	Discharge Hose
Hot Water						
L8347	5/8" x 50'	130 PSI	40° to 180°	3/4" - 11-1/2 (F)	3/4" - 11-1/2 (F)	3/4" - 11-1/2 (F)
Cold Water						
L8349	5/8" x 50'	140 PSI	40° to 140°	3/4" - 11-1/2 (M)	3/4" - 11-1/2 (F)	3/4" - 11-1/2 (M)



Part No. L8347

## Welding

- · Designed for welding & cutting torches.
- · Hose material is reinforced rubber.

Part No.	Hose Size/Length	Max. Working Pressure	Temp. Range (F°)	Reel Inlet MNPT	Source Hose	Discharge Hose
Oxy/Acetylene						
L8363	1/4" x 50'	200 PSI	0-150	9/16" UNF (M)	9/16" UNF (F)	9/16" UNF (F)
Oxy/Fuel*						
L8366	1/4" x 50'	200 PSI	0-150	9/16" UNF (M)	9/16" UNF (F)	9/16" UNF (F)

<sup>\*</sup>Oxy Fuel is designed for MAPP®, Propane & Natural Gases



Part No. L8363

# **Speedy Reel - Manual Rewind**• Hose material is PVC.

Part No.	Hose Included Size/Length	Max. Working Pressure	Reel Max. Pressure	Reel Capacity	Reel Air Inlet	Weight
L8550	3/8" x 50'	350 PSI WP	350 PSI	100' of 3/8" ID	1/4" NPT (M)	17 lbs.



Part No. L8550