

Safety Data Sheet Methyl Fluoride

Section 1: Product and Company Identification

Middlesex Gases & Technologies

292 Second Street P.O. Box 490249 Everett, MA 02149 (617) 387-5050 (800) 649-6704 Fax (617) 387-3537 http://www.middlesexgases.com/

Product Code: Methyl Fluoride

Section 2: Hazards Identification



page 1 of 5

Generated: 06/01/2015

Hazard Classification:Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS # 75-02-5

Chemical Substance	Chemical Family	Trade Names
Methyl Fluoride	halogenated, aliphatic	FLUOROMETHANE; METHANE, FLUORO-; FREON 41; FLUOROMETHANE (CH3F); CH3F; HALACARBON 41; UN2454

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Wash eyes immediately with large amounts of water, occasionally lifting upper and lower lids, until no evidence of chemical remains. Get medical attention immediately.	Not likely route of exposure. Give large amounts of water. DO NOT induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
May explode, gas/air mixtures are heavier than air. Use carbon dioxide, regular dry chemical	Toxic hydrogen fluoride gas	 Full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard	Avoid heat, flames, sparks and other sources	Stop leak if possible without personal risk.
area and deny entry. Ventilate closed spaces	of ignition. Keep out of water supplies and	Reduce vapors with water spray. Remove
before entering.	sewers.	sources of ignition.

Methods for Cleanup	Other Information
Contact emergency personnel, all response personnel should wear self contained breathing apparatus (SCBA) for protection	
against possible exposure.	

Section 7: Handling and Storage

Handling	Storage
Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store in a	Avoid heat, flames,
cool, dry place. Store in a well-ventilated area. Store outside or in a detached building. Subject to storage regulations:	sparks and other
U.S. OSHA 29 CFR 1910.106. Grounding and bonding required. Keep separated from incompatible substances.	sources of ignition.

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

NIOSH REL: TWA 1 ppm C 5 ppm [use 1910.1017]

Engineering Controls

No specific controls are needed.

Eye Protection	Skin Protection	Respiratory Protection
Wear splash resistant safety goggles with a face shield.	Wear appropriate	Full protective fire fighting gear including self
Provide an emergency eye wash fountain and quick drench	chemical resistant	contained breathing apparatus (SCBA) for protection
shower in the immediate work area.	clothing.	against possible exposure.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

F	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
	Gas	Colorless	Clear	N/A	Gas	Faint ethereal	N/A

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
N/A	Not available	Not available	860 F (460 C)	2.6	21.7

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity
-98 F (- 72 C)	-258 F (- 161 C)	19119 mmHg @ 21.1 C	1.6 (Air=1)	0.7 @ 0 C (Water =1)	Insoluble	N/A	Not Available	N/A	Not available

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
46.0	C2H3F	Not available	N/A	N/A	N/A	

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Will polymerize with heat.	Will polymerize with heat.	Mineral-based & clay-based absorbents, dirt/earth, oxidizing materials

Hazardous Decomposition Products		Possibility of Hazardous Reactions	
T	oxic hydrogen fluoride gas is generated in a fire.	Will polymerize with heat.	

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
1600000 mg/m3/4 hour(s) inhalation-rat LC50	Not Available	Nausea, vomiting, diarrhea, headache, drowsiness, symptoms of drunkenness, visual disturbances, bluish skin color, lung congestion, nerve damage, paralysis, convulsions, coma

Eye Irritation	Skin Irritation	Sensitization
Frostbite, blurred vision	Blisters, frostbite	Central nervous system depression, difficulty breathing

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not Available	Not Available	Not Available	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Not Available	Not Available	Not Available	Not Available

Middlesex Gases & Technologies Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

Generated: 06/01/2015

Invertibrate toxicity: Not Available		
Algal toxicity: Not Available		
Phyto toxicity: Not Available		
Other toxicity: Not Available		

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Vinyl fluoride, stabilized	UN1860	2.1	Not available	2.1	Forbidden	150kg	Not available

Canadian Transportation of Dangerous Goods

Shipping Name	UN Number	Class	Packing Group / Risk Group
Vinyl fluoride, stabilized	UN1860	2.1	Not available

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated	Not regulated	Not regulated

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	Yes	Yes	Yes	Yes

SARA 372.65

Not regulated

OSHA Process Safety

Not regulated

State Regulations

CA Proposition 65
Known to cause cancer.

Canadian Regulations

WHMIS Classification
Not determined

National Inventory Status

US Inventory (TSC	A) TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Listed on inventory.	Not listed.	Not determined.

Generated: 06/01/2015

Section 16: Other Information

NFPA Rating

HEALTH=2 FIRE=4 REACTIVITY=2

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

Generated: 06/01/2015