

INSTRUMENT GRADE PIPE FITTINGS

Pipe fittings are commonly used in constructing gas handling systems to join operating components together in a rigid configuration instead of compression fittings. They are well suited to high purity, high pressure, or high vacuum applications. All of the fittings shown below have a minimum pressure rating of 3000 psig. Some stainless steel fittings may be rated at higher operating pressures.

HOW TO ORDER

BRASS P/N	STAINLESS STEEL P/N	DESCRIPTION	
Male Hex Nipple (Fo	connecting female pipe threads)		
2-2MHN-B	2-2MHN-SS	1/8" NPT male x 1/8" NPT male	
4-2MHN-B	4-2MHN-SS	1/4" NPT male x 1/8" NPT male	
4-4MHN-B	4-4MHN-SS	1/4" NPT male x 1/4" NPT male	
8-4MHN-B	8-4MHN-SS	1/2" NPT male x 1/4" NPT male	
8-8MHN-B	8-8MHN-SS	1/2" NPT male x 1/2" NPT male	

Male Hex Long Nipple (For connecting female pipe threads at extended lengths)

4-4MHLN-2.0-SS 4-4MHLN-2.5-SS 4-4MHLN-3.0-SS 4-4MHLN-4.0-SS 1/4" NPT male x 1/4" NPT male (2" long) 1/4" NPT male x 1/8" NPT male (2.5" long) 1/4" NPT male x 1/4" NPT male (3.0" long) 1/4" NPT male x 1/4" NPT male (4.0" long)

Female Hex Coupling (for connecting male pipe threads)

2-2FHC-B 4-2FHC-B 4-4FHC-B 8-4FHC-B 8-8FHC-B 2-2FHC-SS 4-2FHC-SS 4-4FHC-SS 8-4FHC-SS 8-8FHC-SS

1/8" NPT female x 1/8" NPT female	
1/4" NPT female x 1/8" NPT female	
1/4" NPT female x 1/4" NPT female	
1/2" NPT female x 1/4" NPT female	
1/2" NPT female x 1/2" NPT female	

Reducing Bushing (for	joining pipe threads of differen	nt sizes)	
4-2RB-B	4-2RB-SS	1/4" NPT male x 1/8" NPT female	
8-4RB-B	8-4RB-SS	1/2" NPT male x 1/4" NPT female	

Reducing Adapter (for	r joining pipe threads of differer	nt sizes)
4-2RA-B	4-2RA-SS	1/4" NPT female x 1/8" NPT male
8-4RA-B	8-4RA-SS	1/2" NPT female x 1/4" NPT male

Middlesex Gases & Technologies, Inc. 292 Second Street PO Box 490249 Everett, MA 02149

(800) 649-6704 or (617) 387-5050 www.MiddlesexGases.com Info@MiddlesexGases.com











(800) 649-6704 or (617) 387-5050 www.MiddlesexGases.com Info@MiddlesexGases.com

INSTRUMENT GRADE PIPE FITTINGS CONTINUED

HOW TO ORDER

HOW TO ORDER		
BRASS P/N	STAINLESS STEEL P/N	DESCRIPTION
Male Elbow (for conn	ecting female pipe threads at right	angles)
2-2ME-B 4-4ME-B	2-2MEL-SS 4-4MEL-SS	1/8" NPT male x 1/8" NPT male 1/4" NPT male x 1/4" NPT male
2-2FE-B	nnecting male pipe threads at righ	1/8" NPT female x 1/8" NPT female
4-4FE-B	4-4FE-SS	1/4" NPT female x 1/4" NPT female
· · · · · · · · · · · · · · · · · · ·	necting male to female pipe thread	
2-2SE-B 4-4SE-B	2-2SE-SS 4-4SE-SS	1/8" NPT male x 1/8" NPT female 1/4" NPT male x 1/4" NPT female
Female Tee (for conn	ecting male pipe threads in a "T" o	configuration)
2-2-2FT-B 4-4-4FT-B	2-2-2FT-SS 4-4-4FT-SS	1/8" NPT female all ends 1/4" NPT female all ends
Male Tee (for connec	ting male pipe threads in a "T" cor	ifiguration)
2-2-2MT-B	2-2-2MT-SS	1/8" NPT male all ends
4-4-4MT-B	4-4-4MT-SS	1/4" NPT male all ends
Street Tee (for conne	cting pipe threads in a "T" configu	ration female x male x male)
4-4-4ST-B	4-4-4ST-SS	1/4" NPT male x 1/4" NPT female x 1/4" female
·		configuration male x female x male)
4-4-MBT-B	4-4-MBT-SS	1/4" NPT male x 1/4" NPT female x 1/4" female
Pipe Cross (for makin	ng a 4-way connection of male pipe	e threads)
4FX-B	4FX-SS	1/4" NPT female all ends
Hollow Hex Pipe Plua	(to plug a female pipe thread)	
2PHH-B	2PHH-SS	1/8" NPT male
4PHH-B	4PHH-SS	1/4" NPT male